



POLYKEN® 251
Multi-Purpose Metallic Duct Tape


APPLICATIONS

- Sealing heating and air conditioning duct connections.
- General purpose packaging and bundling.
- Holding insulation materials in place.

FEATURES & BENEFITS

- Excellent tensile strength, adhesion, and tack properties.
- Designed for to match flexible ducts, insulation and other aluminum colored surfaces.
- Extremely conformable.
- Will not twist or curl during application.
- Tested in accordance with UL 723.

CONSTRUCTION



PRODUCT DESCRIPTION

Single-Coated Construction

Backing:

- Metallized Polyethylene Coated Cloth

Adhesive:

- Rubber

Colors:

- Metallic

TEST DATA

Test	Typical Value	Typical Value (Metric)	Test Method
Total Thickness	11 mils	279.40 μ	ASTM D 1000
Adhesion to Steel	55 oz./in.	6.02 N/cm	PSTC-1
Adhesion to Backing	48 oz./in.	5.25 N/cm	PSTC-1
Tensile Strength	23 lb./in.	40.28 N/cm	ASTM D 1000
Maximum Performance Temperature	200 F		
Elongation	12%		
Flame Spread	10		
Smoke Developed	5		

**Recommended storage conditions: 40-60% Humidity, 60°F-80°F

The information presented herein was prepared at COVALENCE ADHESIVES, LLC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Covalence's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which COVALENCE ADHESIVES assumes any legal responsibility.