

POLYKEN® 558CA



POLYKEN® 558CA
 Premium Grade UL181 B-FX
 Listed Duct Tape


APPLICATIONS

- Acts as a superior closure system for use with flexible air duct and air connectors
- Recommended for use on UL Listed flexible air ducts in accordance with manufacturer's installation instructions
- Ideal for heating, air conditioning, ventilating, and refrigeration applications
- Suitable for bonding, protecting, holding, repairing, and patching

FEATURES & BENEFITS

- UL 181B-FX Listed (for use with flexible air ducts and closure systems)
- Excellent adhesion and shear (holding power) performance
- Superior quality, performance, and tensile strength
- Excellent resistance to mold growth, humidity, flame spread, smoke generation, and the effects of high temperature
- Printed for easy identification

CONSTRUCTION



PRODUCT DESCRIPTION

Single-Coated Construction

Backing:

- Polyethylene Coated Cloth

Adhesive:

- Rubber

Colors:

- Metallic

TEST DATA

Test	Typical Value	Typical Value (Metric)	Test Method
Total Thickness	14 mils	355.60 μ	ASTM D-1000
Adhesion to Steel	40 oz./in.	4.38 N/cm	PSTC-101
Adhesion to Backing	25 oz./in.	2.74 N/cm	ASTM D-1000
Tensile Strength	50 lb./in.	87.56 N/cm	ASTM D-1000
Flame Spread	10		UL 723
Smoke Developed	20		UL 723
Maximum Performance Temperature	230F		

**Recommended storage conditions: 40-60% Humidity, 60°F-80°F

The information presented herein was prepared at COVALENCE ADHESIVES, LLC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Covalence's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which COVALENCE ADHESIVES assumes any legal responsibility.